



Product Summary

$V_{(BR)DSS}$	$R_{DS(on)TYP}$	I_D
-100V	580m Ω @-10V	-1A
	650m Ω @-4.5V	


Feature

- Trench Technology Power MOSFET
- Low $R_{DS(ON)}$
- Low Gate Charge


Application

- Load Switch
- DC/DC Converter

MARKING




SOT-23



1. GATE
2. SOURCE
3. DRAIN

Schematic diagram



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain - Source Voltage	V_{DS}	-100	V
Gate - Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ^{1,4}	I_D	-1.0	A
Pulsed Drain Current ²	I_{DM}	-4.0	A
Power Dissipation ^{4,5}	P_D	0.77	W
Thermal Resistance from Junction to Ambient ⁵	$R_{\theta JA}$	162	$^\circ\text{C/W}$
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature	T_{STG}	-55~ +150	$^\circ\text{C}$







MOSFET ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Type	Max	Unit
Off Characteristics						
Drain - Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = -250μA	-100			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -80V, V _{GS} = 0V			-1	μA
Gate - Body Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
On Characteristics³						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250μA	-1.5	-2.2	-3.0	V
Drain-source On-resistance	R _{DS(on)}	V _{GS} = -10V, I _D = -1A		580	800	mΩ
		V _{GS} = -4.5V, I _D = -0.5A		650	1000	
Dynamic Characteristics						
Input Capacitance	C _{iss}	V _{DS} = -45V, V _{GS} = 0V, f = 1MHz		300		pF
Output Capacitance	C _{oss}			20		
Reverse Transfer Capacitance	C _{rss}			17		
Gate Resistance	R _g	V _{DS} = 0V, V _{GS} = 0V, f = 1MHz		4.6		Ω
Switching Characteristics						
Total Gate Charge	Q _g	V _{DS} = -10V, V _{GS} = -10V, I _D = -1A		3.2		nC
Gate-source Charge	Q _{gs}			0.5		
Gate-drain Charge	Q _{gd}			1.1		
Turn-on Delay Time	t _{d(on)}	V _{DD} = -10V, V _{GS} = -10V, I _D = -1A, R _G = 2.5Ω		10		ns
Turn-on Rise Time	t _r			32		
Turn-off Delay Time	t _{d(off)}			28		
Turn-off Fall Time	t _f			9		
Source - Drain Diode Characteristics						
Diode Forward Voltage ³	V _{SD}	V _{GS} = 0V, I _S = -1.0A			-1.2	V


Notes :

- 1.The maximum current rating is limited by package.
- 2.Pulse Test : Pulse Width ≤ 10μs, duty cycle ≤ 1%.
- 3.Pulse Test : Pulse Width ≤ 300μs, duty cycle ≤ 2%.
- 4.The power dissipation P_D is limited by T_{J(MAX)} = 150°C.
- 5.Device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A =25°C.

Typical Characteristics



SOT-23 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0	0.100	0	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.150	1.500	0.045	0.059
E1	2.250	2.650	0.089	0.104
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

Attention:

- GreenPower Electronics reserves the right to improve product design function and reliability without notice.
- Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.
- GreenPower Electronics products belong to consumer electronics or other civilian electronic products.